



## NIEL SEAL LIGHT WEIGHT GASKET AND JOINT SEALING COMPOUND

PART NO: N20-66, N20-75

FUNCTION AND APPLICATION: NIEL SEAL LIGHT WEIGHT is a flexible compound for use as a joint sealing compound, caulking compound, corrosive preventative, lubricant, threaded joint dressing, insulating material or filler with packing. Used on head and manifold gaskets of automotive and aircraft engines, water heater fittings gaskets, gas range valves and fitting, pipe threads on dry-cleaning solvent filters, railroad and truck air-brakes, fittings and lines, etc. For all metal-to-metal unions with any kind of gasket.

**OUTSTANDING PROPERTIES:** NIEL SEAL LIGHT WEIGHT is unaffected by water, oil, gasoline, glycerin, steam, gas vapor, exhaust fumes and most hard-to-hold liquids. Withstands extreme temperatures; will not harden, vibration-proof and easy to disassemble for repairs and adjustments. Prevents corrosion and seizing of metal parts. Expands and contracts with temperature changes without affecting seal.

USE DIRECTIONS: NIEL SEAL LIGHT WEIGHT will form seals at a temperature range of 20 to 250°F. Before applying, wipe surfaces dry and clean, then simply spread on. With gaskets: coat joint surfaces and spread evenly. Without gaskets: coat joint surfaces and embed small thread or string as a binder. As a filler: apply as a bond between regular packing and metal surfaces. Do not use thinners.

PRECAUTIONS: Contains a mixture of vegetable oils. May be a skin and eye irritant. Harmful if swallowed.

FIRST AID: In case of eye contact flush with water for at least 15 minutes. For skin contact, wash with soap and water. If ingested, rinse mouth with water; do not induce vomiting. Call poison control center, physician or hospital emergency room immediately.

STORAGE AND HANDLING: Maximum storage temperature 120°F. Keep away from acids, ignition sources and oxidizing agents and keep lid tightly closed when not in use. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals

DISPOSAL: Dispose of product, container and residue in accordance with local laws and regulations.



400 East Tioga Street · Philadelphia, PA · 19134 Phone: 215 - 739 - 9960 • Fax: 215 - 739 - 9963 • www.abbeycolor.com